

FILTRATION SYSTEMS FOR COMMERCIAL APPLICATIONS

ARC
1200



WHO WE ARE?

- For more than a decade Arcotech has managed to position itself as an Israeli market leader in the field of blast protection and CBRN filtration systems for shelters and protected areas.
- Our wide range of solutions provides protection for all, from the smallest system for family protection to systems for the protection of thousands of people.
- Together with our international partners Arcotech solutions help protect thousands of people around the world where it really counts.
- The vast practical and real field experience we have gained through tens of thousands of our successful installations places us as one of the fast-growing companies in its field in the world.

MAIN FEATURES

- ARC series is a series of air filtration systems for commercial and institutional applications.
- Each system includes :Electrical blower, Blast Valve Normally Open, Blast Valve Normally Close and 3 stages of filtration : Dust, Hepa and Chemical.
- Optional high wall / concealed installation to free up high value real estate or room in the shelter.
- Larger flow capacities can be achieved by combining various ARC systems or using our advanced BATTERY series.

ADVANTAGES

- Systems are available in various sizes as 180,240,300,450,600,900,1200 & 1800 m³/h
- Thousands of our units are protecting more than a million people in Israel.
- Complies with SII (Standards Institution of Israel) standard SI 4570 (part 1 to 4)
- Complies with Israel home front command regulation.
- Our systems comply and are certified for SII 4570
- They are regularly and continuously tested by the National Standards Institute.



APPLICATIONS

Institutes



Shopping Malls



Factories



Multiplex





TECHNICAL SPECIFICATIONS - ARC 1200

Technical Specifications	Values	Units
BLAST VALVE NORMALLY OPEN (BVNO 1800 8L)		
Airflow (Ventilation mode)	2400	m ³ /h
Airflow (Filtration mode)	1200	m ³ /h
Returned Pressure durability	>900 (9)	kPa (bar)
Pressure drop (Ventilation mode)	510	mmWC
Pressure drop (Filtration mode)	180	mmWC
AIR FILTER UNIT (AFU 1200)		
Airflow rate	1200	m ³ /h
Pressure Drop at Nominal Flow	100	mmWC
Weight of active carb	120	Kg
Weight of Air filter unit	236	Kg
Efficiency	≥99.995	%
CENTRIFUGAL BLOWER (EBL 2400)		
Airflow (Ventilation mode)	2400	m ³ /h
Airflow (Filtration mode)	1200	m ³ /h
Pressure drop (Ventilation mode)	2760	mmWC
Pressure drop (Filtration mode)	2328	mmWC
Electric motor (Voltage)	400-415	V
Electric motor (Current)	6.2	A
Frequency	50/60	Hz
BLAST VALVE NORMALLY CLOSE (BVNC 600 8Y) X 2		
Airflow (Ventilation mode)	2400	m ³ /h
Airflow (Filtration mode)	1200	m ³ /h
Returned pressure durability	>900 (9)	kPa (bar)
Pressure drop (Ventilation mode)	420	mmWC
Pressure drop (Filtration mode)	200	mmWC

ARC 1200

